



HERCULUX
恒坤光电

Chengdu HercuLux Photoelectric
Technology Co.,Ltd
Product Approval

Approval number :

Customer :

Manufacturer : Chengdu HercuLux Photoelectric Technology Co.,Ltd

PN	Code	Product
HK-WY-35@16-15-D6-21-1g-1	1. 01. 23222	HK Peak 35@16-15 ° lens
HK-WY-35@16-24-D6-21-1g-1	1. 01. 12962	HK Peak 35@16-24 ° lens
HK-WY-35@16-36-D6-21-1g-1	1. 01. 13016	HK Peak 35@16-36 ° lens
HK-WY-35@16-50-D6-21-1g-1	1. 01. 23212	HK Peak 35@16-50 ° lens



Supplier confirmation				Client confirmation			
Proposed		DATE		Qualified <input type="checkbox"/>		DATE	
Project manager		DATE		Unqualified <input type="checkbox"/>			
Audit		DATE		Audit		DATE	
Approved		DATE		Approved		DATE	
Stamp		DATE		Stamp		DATE	

(Confirmation of acceptance by both parties must be signed and sealed)

Factory: Chengdu Shuangliu District, Iot industrial park 2 road HercuLux Photoelectric Park

Phone : 028-85887727 (801) 028-85887990 (801)

Fax : 028-85887730

<http://www.herculux.com/>

Sales Dept: Shenzhen Nanshan District Nanshan Cloud Valley Innovation Industrial Park Comprehensive Service Building,

TEL: 0755-2937 1541

FAX: 0755-2907 5140

*Approval In duplicate , for both supplier and customer.

Disclaimer

Please use this product within the permitted range and environment according to the structure and material of the product. If the usage exceeds the recommended value, please test and verify by yourself. If the product is damaged due to out-of-range use, our company will not be responsible for the warranty.

Product material:

Customized products: The specifications and models of materials used are subject to the agreement between the two parties.

Conventional products: As a product that we continuously research and improve, under the premise of ensuring the quality and availability of the product, our company reserves the right to change the material. If the material specification and model change, without prior notice.

product data:

The measurement data and dimensional tolerances of the 2D drawings in the product data sheet of this acknowledgement are for reference only, and the final size shall prevail in kind.

The measurement data presented in this acknowledgment is a performance test of the product based on our company's internal test conditions and quality requirements, and the reported data is a typical value of the average results of multiple measurements. Therefore, in some cases, the actual product may deviate from the data provided. We reserve the right to notify you in advance of this data.

Product changes and improvements:

Changes and improvements of customized products are subject to the agreement between the two parties in the contract or technical documents.

As the conventional products that we continue to research and improve, our company reserves the right to make technical changes to its products, and reserves the right to make changes to data resulting from improvements without prior notice.

Operation cautions:

1. Please wear clean gloves during product assembly to prevent product surface contamination.
2. Try to avoid touching the optical surface of the lens when taking the lens.
3. When the surface of the product is polluted, please wipe it gently with a soft cotton cloth dipped in analytically pure neutral solvent. It is forbidden to use industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA monomer, etc.) wipe.
4. The lens made of PC should not be exposed to direct sunlight in the storage and use environment. If the lens turns yellow or cracks due to long-term sunlight exposure, our company will not be responsible for the warranty.




HERCULUX
恒坤光电

Basic product information

<http://www.herculux.com/>

Date updated: 2023/4/26


Product Picture:	
Size(L*W*H/Φ*H):	Φ:35mm; H:16.3mm
Material:	PMMA
Efficiency:	\
Temperature(Topr):	Material extreme temperature resistance : -40°C to +100°C long-term use temperature : -40°C to +80°C
FWHM:	15°、24°、36°、50°
Matched LES:	LED:D6
Recommended MAX power:	Not more than 15W

**Technical remark:**

1. The 3D map is not indicated for rounded corners and draft angle.
2. The dimensional tolerances are not specified according to GB/T 14486 2008 MT5.
3. The surface has no flash, shrinkage, bubbles and other defects.
- *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: $Ra < 3.2\mu m$

Optical design			HK Peak 35@16-15 °lens		HK-WY-35@16-15-D6-21-1g-1		
Structure design					1.01.23222		
Review					number of draw	qty	weight
Validation			Material:	PMMA	CDHK		


MT5 Tolerance table	Basic size	<3	3~10	10~24	24~65	65~140	140~250	250~450	>450		
	olerance val	±0.1	±0.15	±0.2	±0.35	±0.50	±0.80	±1.2	±2.0		

**Technical remark:**

1. The 3D map is not indicated for rounded corners and draft angle.
2. The dimensional tolerances are not specified according to GB/T 14486 2008 MT5.
3. The surface has no flash, shrinkage, bubbles and other defects.
- *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: $Ra < 3.2\mu m$

Optical design			HK Peak 35@16-24 %lens		HK-WY-35@16-24-D6-21-1g-1		
Structure design					1.01.12962		
Review					number of draw	qty	weight
Validation			Material: PMMA		CDHK		


MT5 Tolerance table	Basic size	<3	3~10	10~24	24~65	65~140	140~250	250~450	>450		
	olerance val	±0.1	±0.15	±0.2	±0.35	±0.50	±0.80	±1.2	±2.0		

**Technical remark:**

1. The 3D map is not indicated for rounded corners and draft angle.
2. The dimensional tolerances are not specified according to GB/T 14486 2008 MT5.
3. The surface has no flash, shrinkage, bubbles and other defects.
- *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: $Ra < 3.2\mu m$

Optical design			HK Peak 35@16-36 °lens		HK-WY-35@16-36-D6-21-1g-1		
Structure design					1.01.13016		
Review					number of draw	qty	weight
Validation			Material: PMMA		CDHK		

MT5 Tolerance table	Basic size	<3	3~10	10~24	24~65	65~140	140~250	250~450	>450			
	olerance val	±0.1	±0.15	±0.2	±0.35	±0.50	±0.80	±1.2	±2.0			





Technical remark:

1. The 3D map is not indicated for rounded corners and draft angle.
2. The dimensional tolerances are not specified according to GB/T 14486 2008 MT5.
3. The surface has no flash, shrinkage, bubbles and other defects.
- *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: $Ra < 3.2\mu m$

Optical design			HK Peak 35@16-50 %lens		HK-WY-35@16-50-D6-21-1g-1		
Structure design					1.01.23212		
Review					number of draw	qty	weight
Validation			Material: PMMA		CDHK		

MT5 Tolerance table	Basic size	<3	3~10	10~24	24~65	65~140	140~250	250~450	>450			
	olerance val	±0.1	±0.15	±0.2	±0.35	±0.50	±0.80	±1.2	±2.0			



Intensity data:(deg , cd) C0-180



A	I	A	I	A	I	A	I	A	I	A	I
-90.0	0.5197	-58.5	0.3675	-27.0	29.24	4.5	1616	36.0	4.159	67.5	0.4198
-88.5	0.5195	-57.0	0.3804	-25.5	38.02	6.0	1401	37.5	2.938	69.0	0.4293
-87.0	0.5076	-55.5	0.3857	-24.0	50.82	7.5	1150	39.0	1.975	70.5	0.4225
-85.5	0.5077	-54.0	0.3595	-22.5	69.23	9.0	904.4	40.5	0.9429	72.0	0.4244
-84.0	0.4742	-52.5	0.3637	-21.0	95.14	10.5	683.1	42.0	0.4219	73.5	0.4355
-82.5	0.4528	-51.0	0.3660	-19.5	132.4	12.0	493.4	43.5	0.3728	75.0	0.4185
-81.0	0.4535	-49.5	0.3774	-18.0	184.4	13.5	331.3	45.0	0.3765	76.5	0.4237
-79.5	0.4430	-48.0	0.3865	-16.5	258.9	15.0	225.1	46.5	0.3574	78.0	0.4597
-78.0	0.4427	-46.5	0.4018	-15.0	369.9	16.5	157.9	48.0	0.3607	79.5	0.4694
-76.5	0.4558	-45.0	0.4016	-13.5	524.3	18.0	113.0	49.5	0.3616	81.0	0.4713
-75.0	0.4511	-43.5	0.4154	-12.0	716.6	19.5	81.94	51.0	0.3902	82.5	0.5054
-73.5	0.4388	-42.0	0.8413	-10.5	945.2	21.0	60.30	52.5	0.3858	84.0	0.5041
-72.0	0.4376	-40.5	1.956	-9.0	1195	22.5	44.79	54.0	0.3892	85.5	0.4985
-70.5	0.4249	-39.0	2.956	-7.5	1445	24.0	33.70	55.5	0.3841	87.0	0.4997
-69.0	0.4044	-37.5	4.178	-6.0	1662	25.5	25.95	57.0	0.3966	88.5	0.5108
-67.5	0.3854	-36.0	5.700	-4.5	1823	27.0	20.34	58.5	0.3673	90.0	0.5842
-66.0	0.3557	-34.5	7.512	-3.0	1936	28.5	15.96	60.0	0.3644		
-64.5	0.3659	-33.0	10.46	-1.5	1991	30.0	12.47	61.5	0.3729		
-63.0	0.3548	-31.5	13.92	0.0	1985	31.5	9.543	63.0	0.3789		
-61.5	0.3745	-30.0	17.91	1.5	1914	33.0	7.229	64.5	0.3816		
-60.0	0.3808	-28.5	22.89	3.0	1785	34.5	5.580	66.0	0.4018		

Electricity Parameter:

Current I: 0.1000A Power: 3.319W
 Voltage V: 33.20V PF: 1.000

Optical Parameter (Distance=2.410m) :

Equivalent Luminous flux: $\Phi_{\text{eff}} = 249.6\text{lm}$ Efficiency: $\text{Eff} = 75.23\text{lm/W}$
 Diffuse angle: @ (25%): 25.6deg @ (50%): 18.5deg @ (75%): 12.4deg @ (50%): 18.5deg
 Diffuse angle: @ (25%): 25.6deg @ (50%): 18.6deg @ (75%): 12.6deg @ (50%): 18.6deg
 $I_{\text{max}} = 1996\text{cd}$ (C=0.0deg, G=-1.0deg) C0-180Plane $I_{\text{max}} = 1996\text{cd}$ (G=-1.0deg)
 C0-180Plane $I_{0} = 1985\text{cd}$



Intensity data: (deg , cd) C0-180



A	I	A	I	A	I	A	I	A	I	A	I
-90.0	0.7231	-58.5	11.70	-27.0	131.0	4.5	1441	36.0	37.78	67.5	6.453
-88.5	0.7233	-57.0	12.49	-25.5	156.6	6.0	1338	37.5	33.01	69.0	5.848
-87.0	0.8364	-55.5	13.27	-24.0	187.3	7.5	1211	39.0	29.10	70.5	5.187
-85.5	0.9496	-54.0	14.04	-22.5	228.0	9.0	1067	40.5	25.88	72.0	4.548
-84.0	1.165	-52.5	14.93	-21.0	282.7	10.5	913.0	42.0	23.25	73.5	3.884
-82.5	1.529	-51.0	15.91	-19.5	354.9	12.0	760.6	43.5	21.02	75.0	3.264
-81.0	1.937	-49.5	17.04	-18.0	448.5	13.5	618.5	45.0	19.14	76.5	2.764
-79.5	2.359	-48.0	18.40	-16.5	564.3	15.0	496.0	46.5	17.55	78.0	2.269
-78.0	2.856	-46.5	20.05	-15.0	699.3	16.5	395.2	48.0	16.26	79.5	1.776
-76.5	3.360	-45.0	21.99	-13.5	847.5	18.0	306.1	49.5	15.20	81.0	1.297
-75.0	4.029	-43.5	24.35	-12.0	1001	19.5	246.7	51.0	14.28	82.5	0.8966
-73.5	4.707	-42.0	27.16	-10.5	1152	21.0	202.4	52.5	13.48	84.0	0.7782
-72.0	5.353	-40.5	30.67	-9.0	1288	22.5	168.6	54.0	12.72	85.5	0.7629
-70.5	6.018	-39.0	34.92	-7.5	1401	24.0	141.5	55.5	11.98	87.0	0.7457
-69.0	6.672	-37.5	40.13	-6.0	1488	25.5	118.8	57.0	11.25	88.5	0.7219
-67.5	7.341	-36.0	46.60	-4.5	1547	27.0	99.95	58.5	10.54	90.0	0.7107
-66.0	8.011	-34.5	54.77	-3.0	1580	28.5	84.03	60.0	9.795		
-64.5	8.678	-33.0	64.73	-1.5	1593	30.0	70.78	61.5	9.087		
-63.0	9.390	-31.5	77.14	0.0	1589	31.5	59.64	63.0	8.392		
-61.5	10.12	-30.0	91.94	1.5	1567	33.0	50.72	64.5	7.750		
-60.0	10.91	-28.5	109.8	3.0	1518	34.5	43.56	66.0	7.099		

Electricity Parameter:

Current I: 0.1000A Power: 0.3600W
Voltage V: 36.00V PF: 1.000

Optical Parameter (Distance=2.410m) :

Equivalent Luminous flux: $\Phi_{\text{eff}} = 434.0\text{lm}$ Efficiency: $\text{Eff} = 1205.64\text{lm/W}$
Diffuse angle: @ (25%): 35.1deg @ (50%): 25.6deg @ (75%): 17.6deg @ (50%): 25.6deg
Diffuse angle: @ (25%): 35.1deg @ (50%): 25.6deg @ (75%): 17.6deg @ (50%): 25.6deg
 $I_{\text{max}} = 1593\text{cd}$ (C=0.0deg, G=-1.0deg) C0-180Plane $I_{\text{max}} = 1593\text{cd}$ (G=-1.0deg)
C0-180Plane $I_{0} = 1589\text{cd}$



Intensity data:(deg , cd) C0-180



A	I	A	I	A	I	A	I	A	I	A	I
-90.0	0.5084	-58.5	10.13	-27.0	177.9	4.5	950.1	36.0	52.08	67.5	6.133
-88.5	0.4750	-57.0	10.69	-25.5	208.7	6.0	938.7	37.5	42.14	69.0	5.466
-87.0	0.4756	-55.5	11.24	-24.0	245.5	7.5	918.6	39.0	34.85	70.5	4.787
-85.5	0.5210	-54.0	11.71	-22.5	282.7	9.0	887.9	40.5	29.37	72.0	4.139
-84.0	0.6337	-52.5	12.18	-21.0	321.6	10.5	844.6	42.0	25.25	73.5	3.544
-82.5	0.7926	-51.0	12.78	-19.5	364.8	12.0	791.6	43.5	22.01	75.0	2.922
-81.0	1.030	-49.5	13.55	-18.0	414.9	13.5	729.5	45.0	19.49	76.5	2.297
-79.5	1.314	-48.0	14.50	-16.5	473.0	15.0	660.8	46.5	17.54	78.0	1.838
-78.0	1.622	-46.5	15.80	-15.0	539.0	16.5	587.9	48.0	16.05	79.5	1.436
-76.5	1.987	-45.0	17.39	-13.5	610.5	18.0	517.1	49.5	14.89	81.0	1.116
-75.0	2.534	-43.5	19.41	-12.0	681.0	19.5	450.3	51.0	13.95	82.5	0.8129
-73.5	3.127	-42.0	21.96	-10.5	748.4	21.0	389.3	52.5	13.24	84.0	0.6356
-72.0	3.748	-40.5	25.29	-9.0	808.3	22.5	328.0	54.0	12.70	85.5	0.5324
-70.5	4.372	-39.0	29.64	-7.5	857.3	24.0	278.4	55.5	12.14	87.0	0.4908
-69.0	5.012	-37.5	35.77	-6.0	894.3	25.5	233.9	57.0	11.58	88.5	0.4924
-67.5	5.670	-36.0	44.34	-4.5	921.2	27.0	194.1	58.5	10.93	90.0	0.4949
-66.0	6.361	-34.5	56.60	-3.0	939.5	28.5	159.1	60.0	10.19		
-64.5	7.091	-33.0	72.67	-1.5	950.3	30.0	128.8	61.5	9.349		
-63.0	7.863	-31.5	93.03	0.0	955.3	31.5	103.0	63.0	8.502		
-61.5	8.656	-30.0	117.3	1.5	956.4	33.0	81.95	64.5	7.661		
-60.0	9.428	-28.5	146.1	3.0	955.0	34.5	65.14	66.0	6.856		

Electricity Parameter:

Current I: 0.1000A Power: 3.299W
Voltage V: 33.00V PF: 1.000

Optical Parameter (Distance=2.410m) :

Equivalent Luminous flux: $\Phi_{\text{eff}} = 431.6\text{lm}$ Efficiency: $\text{Eff} = 130.85\text{lm/W}$
Diffuse angle: @ (25%): 49.5deg @ (50%): 35.1deg @ (75%): 24.9deg @ (50%): 35.1deg
Diffuse angle: @ (25%): 49.5deg @ (50%): 35.1deg @ (75%): 24.9deg @ (50%): 35.1deg
Imax=956.4cd (C=0.0deg,G=1.5deg) C0-180Plane Imax= 956.4cd(G=1.5deg)
C0-180Plane I0= 955.3cd



Intensity data: (deg , cd) C0-180

A	I	A	I	A	I	A	I	A	I	A	I
-90.0	2.840	-58.5	14.96	-27.0	209.9	4.5	512.3	36.0	50.00	67.5	8.815
-88.5	2.815	-57.0	15.86	-25.5	235.9	6.0	500.5	37.5	42.42	69.0	8.163
-87.0	3.032	-55.5	16.82	-24.0	262.4	7.5	487.5	39.0	36.78	70.5	7.555
-85.5	3.377	-54.0	17.89	-22.5	289.4	9.0	472.9	40.5	32.46	72.0	6.991
-84.0	3.749	-52.5	19.16	-21.0	314.8	10.5	456.9	42.0	29.10	73.5	6.439
-82.5	4.185	-51.0	20.61	-19.5	339.2	12.0	439.4	43.5	26.32	75.0	5.888
-81.0	4.713	-49.5	22.32	-18.0	363.3	13.5	420.0	45.0	24.00	76.5	5.362
-79.5	5.260	-48.0	24.37	-16.5	385.8	15.0	401.1	46.5	22.14	78.0	4.803
-78.0	5.822	-46.5	26.91	-15.0	407.9	16.5	377.0	48.0	20.54	79.5	4.290
-76.5	6.406	-45.0	29.95	-13.5	429.7	18.0	352.1	49.5	19.14	81.0	3.830
-75.0	6.957	-43.5	33.69	-12.0	449.3	19.5	325.9	51.0	17.96	82.5	3.354
-73.5	7.543	-42.0	38.39	-10.5	469.5	21.0	297.5	52.5	16.92	84.0	3.025
-72.0	8.167	-40.5	44.38	-9.0	485.8	22.5	266.1	54.0	15.94	85.5	2.771
-70.5	8.768	-39.0	52.07	-7.5	501.2	24.0	233.4	55.5	15.06	87.0	2.795
-69.0	9.398	-37.5	62.04	-6.0	512.3	25.5	200.0	57.0	14.16	88.5	2.708
-67.5	10.07	-36.0	74.77	-4.5	521.9	27.0	168.1	58.5	13.26	90.0	2.553
-66.0	10.79	-34.5	90.91	-3.0	528.8	28.5	138.7	60.0	12.43		
-64.5	11.52	-33.0	109.7	-1.5	530.7	30.0	113.2	61.5	11.64		
-63.0	12.30	-31.5	131.4	0.0	530.9	31.5	91.49	63.0	10.85		
-61.5	13.13	-30.0	155.8	1.5	528.8	33.0	73.90	64.5	10.13		
-60.0	14.00	-28.5	182.3	3.0	522.0	34.5	60.10	66.0	9.473		

Electricity Parameter:

Current I: 0.1000A Power: 3.578W
Voltage V: 35.79V PF: 1.000


Optical Parameter (Distance=2.559m) :

Equivalent Luminous flux: $\Phi_{\text{eff}} = 366.1\text{lm}$ Efficiency: $\text{Eff} = 102.32\text{lm/W}$
Diffuse angle: @ (25%): 60.2deg @ (50%): 46.3deg @ (75%): 30.7deg @ (50%): 46.3deg
Diffuse angle: @ (25%): 60.2deg @ (50%): 46.3deg @ (75%): 30.8deg @ (50%): 46.3deg
 $I_{\text{max}} = 531.1\text{cd}$ (C=0.0deg, G=-1.0deg) C0-180Plane $I_{\text{max}} = 531.1\text{cd}$ (G=-1.0deg)
C0-180Plane $I_0 = 530.9\text{cd}$

		Standard size	Upper Size limit	Lower size limit	Test result1	Test result2	Test result3	Test result4	Test result5	Test result6	Test result7	Test result8	Judgment	Remarks
1.Size	diameter	35			35.06	35.03	35.07	35.05	35.09	35.08	35.08	35.08		Test environment: In 20℃ -25℃ environment to achieve thermal equilibrium after the test.
	height1	16.3			16.27	16.29	16.26	16.31	16.32	16.32	16.3	16.28		
	height2	2			2.08	2.09	2.1	2.11	2.1	2.13	2.12	2.09		
	Gate shear can not affect the appearance of the lamp													
	See attachment "Appearance Inspection Standards"													
2.Appearance Quality		See attachment "Appearance Inspection Standards"	E	No burr		No burr		No burr		No burr		OK		
				No stains		No stains		No stains		No stains				
3.Material		PMMA					Color		Transparent				OK	
4.Optical index	Testing LED		CREE 1304											
	The size and rated power of the light-emitting surface (LES) of the COB recommended by this lens should conform to the parameters in the product basic information table. if it is required to be out of range. According to the heat dissipation capability of the lamp and the actual conditions of the use environment, the lens should be fully tested and tested to prevent the lens life.													
	FWHM		See light distribution curve											
	angle				18.3	18.5	18.4	18.2	18.2	18.3	18.3	18.2		
	-value (CD/L				7.69	8.02	8.11	8.31	8.17	8.94	7.83	8.28		
	Efficiency				70.4%	67.1%	66.6%	65.8%	66.8%	67.7%	70.6%	70.6%		
	Facula		See the signature sample											
Comprehensive judgment		Qualified												

Remarks:

- 1、 Tool Number: V- Vernier Caliper 2D- Quadratic H-Height Gauge M-Tool Microscope P-Needle T-Thick Gauge R- Radius Gauge E- Visual.
- 2、 Ambient temperature on the size of the product refer to the table on the right




Precautions:

1. Please wear clean gloves during the lens assembly process to prevent the lens surface from being contaminated.
2. Try to avoid touching the total reflection surface when taking the lens.
3. The lens surface is contaminated. Only use a soft cotton cloth dipped in analytically pure neutral solvent to wipe gently. Do not wipe with industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA Body, etc.).
4. The working temperature of the lens should be within the temperature resistance limit of the lens material. Exceeding the temperature resistance limit will cause the lens to crack or melt and affect the service life of the lens. It is recommended that the upper surface temperature of the LED colloid should be less than 120 degrees.

		Standard size	Upper Size limit	Lower size limit	Test result1	Test result2	Test result3	Test result4	Test result5	Test result6	Test result7	Test result8	Judgment	Remarks
1.Size	diameter	35			34.87	34.89	34.88	34.86	34.88	34.84	34.87	34.84		Test environment: In 20 ℃ -25 ℃ environment to achieve thermal equilibrium after the test.
	height1	16.3			16.24	16.31	16.24	16.23	16.24	16.22	16.21	16.23		
	height2	2			2.03	2.13	2.05	2.01	2.04	2.02	2.01	2.04		
	Gate shear can not affect the appearance of the lamp													
	See attachment "Appearance Inspection Standards"													
2.Appearance Quality	See attachment "Appearance Inspection Standards"	E	No burr		No burr		No burr		No burr		No burr		OK	
			No stains		No stains		No stains		No stains					
3.Material		PMMA					Color		Transparent				OK	
4.Optical index	Testing LED		CREE 1304(Black bracket bowl)											
	The size and rated power of the light-emitting surface (LES) of the COB recommended by this lens should conform to the parameters in the product basic information table. if it is required to be out of range. According to the heat dissipation capability of the lamp and the actual conditions of the use environment, the lens should be fully tested and tested to prevent the lens life.													
	FWHM		See light distribution curve											
	angle				25.6	25.5	25.7	25.5	25.3	25.3	25.6	25.6		
	-value (CD/L				3.67	3.63	3.28	3.46	3.51	3.51	3.38	3.42		
	Efficiency				85.0%	86.0%	85.7%	86.3%	87.0%	86.5%	86.1%	87.0%		
Facula		See the signature sample												
Comprehensive judgment		Qualified												

Remarks:

- 1、 Tool Number: V- Vernier Caliper 2D- Quadratic H-Height Gauge M-Tool Microscope P-Needle T-Thick Gauge R- Radius Gauge E- Visual.
- 2、 Ambient temperature on the size of the product refer to the table on the right




Precautions:

1. Please wear clean gloves during the lens assembly process to prevent the lens surface from being contaminated.
2. Try to avoid touching the total reflection surface when taking the lens.
3. The lens surface is contaminated. Only use a soft cotton cloth dipped in analytically pure neutral solvent to wipe gently. Do not wipe with industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA Body, etc.).
4. The working temperature of the lens should be within the temperature resistance limit of the lens material. Exceeding the temperature resistance limit will cause the lens to crack or melt and affect the service life of the lens. It is recommended that the upper surface temperature of the LED colloid should be less than 120 degrees.

1.Size		Standard size	Upper Size limit	Lower size limit	Test result1	Test result2	Test result3	Test result4	Test result5	Test result6	Test result7	Test result8	Judgment	Remarks
	diameter	35			34.91	34.95	34.95	34.93	34.93	34.93	34.95	34.97		Test environment: In 20 ℃ -25 ℃ environment to achieve thermal equilibrium after the test.
	height1	16.3			16.41	16.4	16.42	16.42	16.4	16.4	16.42	16.42		
	height2	2			2.14	2.15	2.15	2.16	2.15	2.14	2.14	2.16		
	Gate shear can not affect the appearance of the lamp													
	See attachment "Appearance Inspection Standards"													
2.Appearance Quality		See attachment "Appearance Inspection Standards"	E	No burr		No burr		No burr		No burr		OK		
				No stains		No stains		No stains		No stains				
3.Material		PMMA					Color		Transparent				OK	
4.Optical index	Testing LED		CREE 1304(Black bracket bowl)											
	The size and rated power of the light-emitting surface (LES) of the COB recommended by this lens should conform to the parameters in the product basic information table. if it is required to be out of range. According to the heat dissipation capability of the lamp and the actual conditions of the use environment, the lens should be fully tested and tested to prevent the lens life.													
	FWHM		See light distribution curve											
	angle				35.1	35.3	35.1	34.8	35.4	34.7	35.4	34.8		
	-value (CD/L				2.22	2.25	2.26	2.26	2.20	2.27	2.21	2.22		
	Efficiency				86.0%	86.3%	85.7%	86.0%	86.3%	84.8%	85.5%	87.0%		
Facula		See the signature sample												
Comprehensive judgment		Qualified												

Remarks:

- 1、 Tool Number: V- Vernier Caliper 2D- Quadratic H-Height Gauge M-Tool Microscope P-Needle T-Thick Gauge R- Radius Gauge E- Visual.
- 2、 Ambient temperature on the size of the product refer to the table on the right




Precautions:

1. Please wear clean gloves during the lens assembly process to prevent the lens surface from being contaminated.
2. Try to avoid touching the total reflection surface when taking the lens.
3. The lens surface is contaminated. Only use a soft cotton cloth dipped in analytically pure neutral solvent to wipe gently. Do not wipe with industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA Body, etc.).
4. The working temperature of the lens should be within the temperature resistance limit of the lens material. Exceeding the temperature resistance limit will cause the lens to crack or melt and affect the service life of the lens. It is recommended that the upper surface temperature of the LED colloid should be less than 120 degrees.

1.Size		Standard size	Upper Size limit	Lower size limit	Test result1	Test result2	Test result3	Test result4	Test result5	Test result6	Test result7	Test result8	Judgment	Remarks
	diameter	35			35.2	35.22	35.18	35.14	35.22	35.2	35.14	35.17		Test environment: In 20 ℃ -25 ℃ environment to achieve thermal equilibrium after the test.
	height1	16.3			16.32	16.35	16.34	16.32	16.35	16.33	16.32	16.32		
	height2	2			2.18	2.18	2.2	2.18	2.2	2.2	2.18	2.2		
	Gate shear can not affect the appearance of the lamp													
	See attachment "Appearance Inspection Standards"													
2.Appearance Quality		See attachment "Appearance Inspection Standards"	E	No burr		No burr		No burr		No burr		OK		
				No stains		No stains		No stains		No stains				
3.Material		PMMA					Color		Transparent				OK	
4.Optical index	Testing LED		CREE 1304(Black bracket bowl)											
	The size and rated power of the light-emitting surface (LES) of the COB recommended by this lens should conform to the parameters in the product basic information table. if it is required to be out of range. According to the heat dissipation capability of the lamp and the actual conditions of the use environment, the lens should be fully tested and tested to prevent the lens life.													
	FWHM		See light distribution curve											
	angle				46.3	47.4	46.4	46.1	46.6	48.8	46.9	46.7		
	value (CD/L													
	Efficiency				85.0%	84.0%	83.0%	83.5%	83.9%	84.7%	85.1%	85.3%		
Facula		See the signature sample												
Comprehensive judgment		Qualified												

Remarks:

- 1、 Tool Number: V- Vernier Caliper 2D- Quadratic H-Height Gauge M-Tool Microscope P-Needle T-Thick Gauge R- Radius Gauge E- Visual.
- 2、 Ambient temperature on the size of the product refer to the table on the right



Precautions:




1. Please wear clean gloves during the lens assembly process to prevent the lens surface from being contaminated.
2. Try to avoid touching the total reflection surface when taking the lens.
3. The lens surface is contaminated. Only use a soft cotton cloth dipped in analytically pure neutral solvent to wipe gently. Do not wipe with industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA Body, etc.).
4. The working temperature of the lens should be within the temperature resistance limit of the lens material. Exceeding the temperature resistance limit will cause the lens to crack or melt and affect the service life of the lens. It is recommended that the upper surface temperature of the LED colloid should be less than 120 degrees.

PN		HK-WY-35@16-15-D6-21-1g-1	Product Name	HK Peak 35@16-15 °lens			
Product material		PMMA					
Package diagram		<div><p>Single Vacuum package Box package</p></div>					
Product packing		32	A/ Box	4	pcs/Layer		
		14	Layer/Box	1288	A/ Carton		
Packaging Materials	NO.	Part No	Part name	Size	Dosage	Unit	Remarks
	1	2.07.0075	Blister box	23cm*21cm	56	BAG	
	2	2.08.0001	PE film	30cm*30cm	56	PCS	
	3	2.06.0005	Reel label paper	6.2cm*8cm	56	PCS	
	4	2.06.0005	Box label paper	6.2cm*9.2cm	1	PCS	
	5	2.06.0003	big plate	46.8cm*42.8cm	15	PCS	
	6	2.06.0015	big flat carton	48cm*44cm*19cm	1	PCS	
Remarks	The loose packing is not subject to this specification. Customer's requirements shall prevail						

Special notice

When glue pass through holes, columns and other structures, or part of the thin structure, will form a weld line. The product which uses multi-point injection welding line will appear because of the combination of sol, as shown below:

Сыниен



The joint line will appear in the red line

Please note :

The appearance of lines in the structure of the product as well as at the screw hole is a normal phenomenon, will not affect the actual use of the product, and can not be avoided at this stage.

Appearance inspection standards

1 Operating procedures

1.1.1 Sampling standards, sampling plan and AQL

Test level : GB/T2828.1-2012 The first part is according to the acceptance quality limit (AQL) retrieval batch inspection sampling plan, general inspection level II level, CR class defect coefficient 0, MA defect rejection level AQL = 0.65, MI class defect rejection level AQL = 1.0; defect level please see 5.4.

2 Code table

Code	Code description	Unit	Code		Code description	Unit
N	Amount/pcs	pcs	D		Diameter	mm
L	Length	mm	H		Depth	mm
W	Width	mm	DS		Distance	mm
S	Proportion	mm ²	SS		Offset	mm

3 Test conditions

3.1 Sight distance and working hours: Sight distance should be 30-35cm, each side of the inspection time does not exceed 12s, the visual angle of 45-135 degrees;

3.2 Light: 2x40w cool white fluorescent lamp, the light source is 500-550mm away from the lens surface; in order to make the appearance defect can be correctly recognized, the illumination should be 500-1000Lux, and the observation time is 10 seconds.

3.3 Visual inspection staff should be 1.0 (including corrected visual acuity) above, no color blindness, color weakness.

4 Appearance inspection standards

Test items	Judging standard	Inspection equipment	Defect level		
		Testing method	MI	MA	CR
Check the sample	When start the machine and process, all products have to check the appearance of the sample, the appearance of the sample is divided into qualified samples and limited samples.	Sample comparison , visual			√
	1: Qualified sample refers to the appearance and structure standard of the product which recognized by the client, the sample size should be confirmed before mass production;				

	2: The limited sample refers to the limit of a particular exceptionally developed sample. Limit the sample only for its specific point of exception to confirm; The priority is higher than the other criteria in this table. When there is a limited sample, the limit sample shall prevail.				
Raw edge	Not allowed to affect the size and assembly	Visual, point card		√	
Scratch	1: Non-optical surface and non-exposed surface scratches should be visually insignificant and the length is less than 1/10 of the maximum surface size.	Visual, point card, calipers		√	
Fingerprint	Fingerprints are not allowed on all products	Visual		√	
Foreign objects, black spots, white spots	The product may not be attached to foreign objects, including oil, fiber, dregs of water gap and so on				√
Deformation	Insufficient filling shall not affect the appearance of the assembly and the exposed surfaces.	Visual, feeler			√
Poor ejection	Products may not appear bad ejection, including no convex top, thimble printed on the assembly surface shall not be higher than the product surface, non-assembled surface thimble height should not exceed the product size tolerances; thimble printing should be less than the product surface and no more than 0.3; thimble surface treatment should be consistent with the product side.	Visual, point card		√	
	Ejection strain: the optical surface and the appearance of the exposed surface after assembly are not allowed to have a strain, and the structural surface does not allow visual obvious strain.				
Insufficient filling	Insufficient filling shall not affect the appearance of the assembly and the exposed surfaces , The signature sample shall prevail.	Visual, point card		√	
Shrink	When the entire surface of the product shrinks, the optical properties and dimensions must meet the requirements, and the visual will not significantly affect the appearance.Part shrink reference point defects	Visual, point card		√	
Flow marks、Welding line	1 : Product does not allow the presence of flow marks and welding lines unless the structure can not be avoided;	Visual		√	
	2: The remaining flow marks shall not appear in the optical surface, a single $L \leq 10\text{mm}$, no more than two				
Bubble	No bubbles are allowed	Visual		√	

Foreign objects, black spots, white spots	Not obvious or $D \leq 0.3\text{mm}$ black spots and foreign bodies in the area of 100x100mm not more than 1; Exceeded foreign matter black spots is judged bad.	Visual, point card	√		
Damaged	No damage is allowed	Visual			√
Cold glue	Optical surface may not have cold glue, non-optical surface cold glue should meet the visual is not obvious.	Visual	√		
Bad incision	1: Do not affect the product size, shall not penetrate the optical surface, the cut should be smooth;	Visual			√
	2: Laser cutting products, the optical surface burns shall not occur after the processing is completed. Beading must not affect product installation				
	3: Three molds and hot runner gate shall not appear residue.				
Scrub	Scrub surface should be uniform, off the scrub phenomenon should not be obvious , A single off scrub imprint requires $D \leq 1\text{ mm}$ and no more than 1 area within a 50x50 mm area	Visual		√	



HERCULUX
恒坤光电

Chengdu HercuLux Photoelectric
Technology Co.,Ltd
Product Approval

Approval number:

Customer:

Manufacturer: Chengdu HercuLux Photoelectric Technology Co.,Ltd

PN	Code	Product
HK-WY-35@16-15-D6-21-1g-1-V	1. 01. 23354	HK Peak 35@16-15 ° lens (V)
HK-WY-35@16-24-D6-21-1g-1-V	1. 01. 23353	HK Peak 35@16-24 ° lens (V)
HK-WY-35@16-36-D6-21-1g-1-V	1. 01. 23432	HK Peak 35@16-36 ° lens (V)



Supplier confirmation				Client confirmation			
Proposed		DATE		Qualified <input type="checkbox"/>		DATE	
Project manager		DATE		Unqualified <input type="checkbox"/>		DATE	
Audit		DATE		Audit		DATE	
Approved		DATE		Approved		DATE	
Stamp		DATE		Stamp		DATE	

(Confirmation of acceptance by both parties must be signed and sealed)

Factory: Chengdu Shuangliu District, lot industrial park 2 road HercuLux Photoelectric Park

Phone: 028-85887727 (801) 028-85887990 (801)

Fax: 028-85887730

<http://www.herculux.com/>

Sales Dept: Shenzhen Nanshan District Nanshan Cloud Valley Innovation Industrial Park Comprehensive Service Building,

TEL: 0755-2937 1541

FAX: 0755-2907 5140

*Approval In duplicate, for both supplier and customer.

Please use this product within the permitted range and environment according to the structure and material of the product. If the usage exceeds the recommended value, please test and verify by yourself. If the product is damaged due to out-of-range use, our company will not be responsible for the warranty.

Product material:

Customized products: The specifications and models of materials used are subject to the agreement between the two parties.

Conventional products: As a product that we continuously research and improve, under the premise of ensuring the quality and availability of the product, our company reserves the right to change the material. If the material specification and model change, without prior notice.

product data:

The measurement data and dimensional tolerances of the 2D drawings in the product data sheet of this acknowledgement are for reference only, and the final size shall prevail in kind.

The measurement data presented in this acknowledgment is a performance test of the product based on our company's internal test conditions and quality requirements, and the reported data is a typical value of the average results of multiple measurements. Therefore, in some cases, the actual product may deviate from the data provided. We reserve the right to notify you in advance of this data.

Product changes and improvements:

Changes and improvements of customized products are subject to the agreement between the two parties in the contract or technical documents.

As the conventional products that we continue to research and improve, our company reserves the right to make technical changes to its products, and reserves the right to make changes to data resulting from improvements without prior notice.

Operation cautions:

1. Please wear clean gloves during product assembly to prevent product surface contamination.
2. Try to avoid touching the optical surface of the lens when taking the lens.
3. When the surface of the product is polluted, please wipe it gently with a soft cotton cloth dipped in analytically pure neutral solvent. It is forbidden to use industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA monomer, etc.) wipe.
4. The lens made of PC should not be exposed to direct sunlight in the storage and use environment. If the lens turns yellow or cracks due to long-term sunlight exposure, our company will not be responsible for the warranty.




HERCULUX
恒坤光电

Basic product information

<http://www.herculux.com/>

Date updated: 2023/7/11




Product Picture:	
Size(L*W*H/Φ*H):	15°: Φ:35mm; H:16.5mm 24°: Φ:35mm; H:17mm 36°: Φ:35mm; H:16.3mm
Material:	PMMA
Efficiency:	\
Temperature(Topr):	Material extreme temperature resistance: -40°C to +100°C long-term use temperature: -40°C to +80°C
FWHM:	15°、24°、36°
Matched LES:	LED:D6
Recommended MAX power:	Not more than 15W



技术要求:
1、未注圆角及拔模斜度按3D图。
2、未注尺寸公差按右表。
3、表面无飞边, 缩水, 气泡等缺陷。
*4、灯具采用胶圈防水时: 要求散热器与胶圈的接触面的粗糙度: $Ra < 3.2\mu m$

Technical remark:
1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3, The surface has no flash, shrinkage, bubbles and other defects.
*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: $Ra < 3.2\mu m$

基本尺寸	公差值										
Basic size	Tolerance value	2						4			
<3	± 0.1	1						3			
3~10	± 0.15	序号	更改标记	更改内容	更改日期	签名	序号	更改标记	更改内容	更改日期	签名
10~24	± 0.20	Item	Change mark	Change content	Change date	Signature	Item	Change mark	Change content	Change date	Signature
24~65	± 0.35	光学设计			Title: HK 无影35@16-15度透镜(V) HK Peak 35@16-15 °lens(V)		Drawing No. HK-WY-35@16-15-D6-21-1g-1-V		Part No. 1.01.23354		
65~140	± 0.50	结构设计									
140~250	± 0.80	审核									
250~450	± 1.2	Verify									
>450	± 2.0	审定			材料	PMMA	CDHK				
		Approval			Material:						






技术要求:
1、未注圆角及拔模斜度按3D图。
2、未注尺寸公差按右表。
3、表面无飞边, 缩水, 气泡等缺陷。
*4、灯具采用胶圈防水时: 要求散热器与胶圈的接触面的粗糙度: $Ra < 3.2\mu m$

Technical remark:
1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: $Ra < 3.2\mu m$



基本尺寸	公差值
Basic size	Tolerance value
< 3	± 0.1
3~10	± 0.15
10~24	± 0.20
24~65	± 0.35
65~140	± 0.50
140~250	± 0.80
250~450	± 1.2
> 450	± 2.0

2					4					
1					3					
序号	更改标记	更改内容	更改日期	签名	序号	更改标记	更改内容	更改日期	签名	
Item	Change mark	Change content	Change date	Signature	Item	Change mark	Change content	Change date	Signature	
光学设计			Title: HK 无影35@16-24度透镜(V) HK Peak 35@16-24 °lens(V)				Drawing No. HK-WY-35@16-24-D6-21-1g-1-V			
结构设计										
审核			材料: PMMA				Part No. 1.01.23353			
审定							CDHK			
Approval										



1. Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
- *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: $Ra < 3.2\mu m$

基本尺寸	公差值										
Basic size	Tolerance value	2					4				
<3	±0.1	1					3				
3~10	±0.15	序号	更改标记	更改内容	更改日期	签 名	序号	更改标记	更改内容	更改日期	签 名
10~24	±0.20	Item	Change mark	Change content	Change date	Signature	Item	Change mark	Change content	Change date	Signature
24~65	±0.35	光 学 设计 Optical design				Title: HK 无影35@16-36度透镜(V) HK Peak 35@16-36 °lens(V)		Drawing No. HK-WY-35@16-36-D6-21-1g-1-V			
65~140	±0.50	结 构 设计 Structural design						Part No.			
140~250	±0.80	审 核 Verify						1.01.23432			
250~450	±1.2	审 定 Approval						CDHK			
>450	±2.0					材料 Material:	PMMA				



Intensity data:(deg , cd) C0-180

A	I	A	I	A	I	A	I	A	I	A	I
-90.0	0.2599	-58.5	0.3312	-27.0	13.02	4.5	1975	36.0	0.7540	67.5	0.4686
-88.5	0.2823	-57.0	0.3333	-25.5	22.03	6.0	1690	37.5	0.6829	69.0	0.4454
-87.0	0.2821	-55.5	0.3468	-24.0	32.58	7.5	1331	39.0	0.5981	70.5	0.4812
-85.5	0.2930	-54.0	0.3390	-22.5	46.34	9.0	1007	40.5	0.5580	72.0	0.4385
-84.0	0.3167	-52.5	0.4018	-21.0	65.18	10.5	741.5	42.0	0.4293	73.5	0.4316
-82.5	0.3390	-51.0	0.4205	-19.5	91.37	12.0	533.1	43.5	0.3655	75.0	0.4304
-81.0	0.3282	-49.5	0.4719	-18.0	126.7	13.5	366.1	45.0	0.4141	76.5	0.3973
-79.5	0.3705	-48.0	0.4341	-16.5	172.4	15.0	240.1	46.5	0.4026	78.0	0.4258
-78.0	0.3602	-46.5	0.5021	-15.0	231.8	16.5	172.6	48.0	0.4119	79.5	0.4005
-76.5	0.3148	-45.0	0.4833	-13.5	316.3	18.0	126.5	49.5	0.4203	81.0	0.4471
-75.0	0.2494	-43.5	0.5039	-12.0	447.8	19.5	91.76	51.0	0.3682	82.5	0.4513
-73.5	0.2627	-42.0	0.5622	-10.5	630.2	21.0	65.96	52.5	0.3696	84.0	0.4873
-72.0	0.3091	-40.5	0.5902	-9.0	870.4	22.5	47.16	54.0	0.3108	85.5	0.4999
-70.5	0.3547	-39.0	0.6414	-7.5	1164	24.0	33.58	55.5	0.3564	87.0	0.5637
-69.0	0.2938	-37.5	0.7522	-6.0	1496	25.5	23.38	57.0	0.3086	88.5	0.6167
-67.5	0.3138	-36.0	0.8462	-4.5	1823	27.0	15.14	58.5	0.3384	90.0	0.5988
-66.0	0.2739	-34.5	0.9472	-3.0	2054	28.5	7.892	60.0	0.3531		
-64.5	0.3543	-33.0	1.149	-1.5	2192	30.0	2.798	61.5	0.3503		
-63.0	0.3246	-31.5	1.406	0.0	2247	31.5	1.693	63.0	0.4327		
-61.5	0.2970	-30.0	1.745	1.5	2240	33.0	1.322	64.5	0.4909		
-60.0	0.2667	-28.5	5.274	3.0	2152	34.5	0.9647	66.0	0.4692		

Electricity Parameter:

Current I: 0.3000A Power: 1.799W

Voltage V: 6.000V PF: 1.000

Optical Parameter (Distance=2.410m) :



Equivalent Luminous flux: Φ_{eff} = 226.2lm Efficiency: Eff = 125.76lm/W

Diffuse angle: @ (25%) : 22.6deg @ (50%) : 16.0deg @ (75%) : 11.1deg @ (50%) : 16.0deg

Diffuse angle: @ (25%) : 22.7deg @ (50%) : 16.0deg @ (75%) : 11.1deg @ (50%) : 16.0deg

I_{max} = 2251cd (C=0.0deg, G=0.5deg) C0-180Plane I_{max} = 2251cd (G=0.5deg)

C0-180Plane I_0 = 2247cd



Intensity data:(deg , cd) C0-180

A	I	A	I	A	I	A	I	A	I	A	I
-90.0	3.333	-58.5	5.502	-27.0	69.56	4.5	1833	36.0	24.15	67.5	3.226
-88.5	3.287	-57.0	6.033	-25.5	86.49	6.0	1662	37.5	21.60	69.0	3.079
-87.0	3.208	-55.5	6.716	-24.0	108.7	7.5	1458	39.0	19.39	70.5	2.967
-85.5	3.174	-54.0	7.583	-22.5	138.8	9.0	1240	40.5	17.55	72.0	2.845
-84.0	3.072	-52.5	8.549	-21.0	177.7	10.5	1018	42.0	15.90	73.5	2.704
-82.5	2.928	-51.0	9.513	-19.5	228.3	12.0	806.9	43.5	14.39	75.0	2.664
-81.0	2.933	-49.5	10.67	-18.0	297.0	13.5	620.7	45.0	12.97	76.5	2.604
-79.5	2.844	-48.0	11.91	-16.5	389.6	15.0	472.9	46.5	11.68	78.0	2.628
-78.0	2.814	-46.5	13.24	-15.0	508.7	16.5	357.7	48.0	10.46	79.5	2.620
-76.5	2.867	-45.0	14.55	-13.5	661.5	18.0	266.6	49.5	9.345	81.0	2.640
-75.0	2.881	-43.5	16.07	-12.0	848.1	19.5	203.7	51.0	8.203	82.5	2.700
-73.5	2.968	-42.0	17.51	-10.5	1062	21.0	156.6	52.5	7.205	84.0	2.852
-72.0	3.024	-40.5	19.29	-9.0	1281	22.5	122.0	54.0	6.472	85.5	2.895
-70.5	3.162	-39.0	21.36	-7.5	1495	24.0	96.47	55.5	5.763	87.0	3.044
-69.0	3.407	-37.5	23.66	-6.0	1691	25.5	77.03	57.0	5.249	88.5	3.015
-67.5	3.565	-36.0	26.36	-4.5	1856	27.0	62.27	58.5	4.856	90.0	3.051
-66.0	3.774	-34.5	29.61	-3.0	1974	28.5	50.89	60.0	4.403		
-64.5	4.015	-33.0	33.70	-1.5	2041	30.0	42.28	61.5	4.054		
-63.0	4.403	-31.5	39.18	0.0	2060	31.5	35.76	63.0	3.845		
-61.5	4.632	-30.0	46.65	1.5	2036	33.0	30.88	64.5	3.586		
-60.0	5.079	-28.5	56.61	3.0	1961	34.5	27.16	66.0	3.383		

Electricity Parameter:

Current I: 0.1000A Power: 110.0W

Voltage V: 220.0V PF: 1.000

Optical Parameter(Distance=2.410m):

Equivalent Luminous flux: $\Phi_{\text{eff}} = 378.1\text{lm}$ Efficiency: $\text{Eff} = 3.44\text{lm/W}$



Diffuse angle: @ (25%): 29.4deg @ (50%): 21.1deg @ (75%): 13.9deg @ (50%): 21.1deg

Diffuse angle: @ (25%): 29.4deg @ (50%): 21.1deg @ (75%): 13.9deg @ (50%): 21.1deg

Imax=2060cd (C=0.0deg, G=0.0deg)

C0-180Plane Imax= 2060cd(G=0.0deg)

C0-180Plane IO= 2060cd



Intensity data:(deg , cd) C0-180

A	I	A	I	A	I	A	I	A	I	A	I
-90.0	0.8248	-58.5	0.4484	-27.0	150.3	4.5	1099	36.0	23.34	67.5	0.5239
-88.5	0.7567	-57.0	0.4369	-25.5	190.0	6.0	1046	37.5	10.61	69.0	0.5377
-87.0	0.7115	-55.5	0.4180	-24.0	233.2	7.5	980.0	39.0	2.818	70.5	0.5536
-85.5	0.6779	-54.0	0.4201	-22.5	281.1	9.0	900.0	40.5	0.5936	72.0	0.5466
-84.0	0.6447	-52.5	0.4265	-21.0	332.3	10.5	807.6	42.0	0.4184	73.5	0.5597
-82.5	0.6344	-51.0	0.4406	-19.5	389.9	12.0	703.7	43.5	0.4142	75.0	0.5688
-81.0	0.6224	-49.5	0.4834	-18.0	454.1	13.5	604.1	45.0	0.4217	76.5	0.5800
-79.5	0.6327	-48.0	0.4472	-16.5	529.1	15.0	519.1	46.5	0.4293	78.0	0.6291
-78.0	0.6320	-46.5	0.4382	-15.0	613.0	16.5	446.6	48.0	0.4302	79.5	0.6485
-76.5	0.6184	-45.0	0.4355	-13.5	704.6	18.0	388.7	49.5	0.4338	81.0	0.6811
-75.0	0.5954	-43.5	0.4354	-12.0	797.9	19.5	339.7	51.0	0.4420	82.5	0.6846
-73.5	0.5838	-42.0	0.4963	-10.5	888.1	21.0	298.2	52.5	0.4939	84.0	0.6991
-72.0	0.5310	-40.5	1.205	-9.0	968.3	22.5	267.1	54.0	0.4438	85.5	0.7217
-70.5	0.5434	-39.0	3.492	-7.5	1036	24.0	237.0	55.5	0.4355	87.0	0.7269
-69.0	0.5096	-37.5	7.516	-6.0	1090	25.5	206.8	57.0	0.4496	88.5	0.7582
-67.5	0.4909	-36.0	13.76	-4.5	1128	27.0	176.1	58.5	0.4464	90.0	0.7807
-66.0	0.4773	-34.5	23.30	-3.0	1155	28.5	145.4	60.0	0.4462		
-64.5	0.4873	-33.0	36.94	-1.5	1172	30.0	115.4	61.5	0.4519		
-63.0	0.4730	-31.5	56.62	0.0	1177	31.5	86.97	63.0	0.4648		
-61.5	0.4600	-30.0	81.99	1.5	1165	33.0	61.71	64.5	0.4895		
-60.0	0.4389	-28.5	113.5	3.0	1139	34.5	40.50	66.0	0.5099		

Electricity Parameter:

Current I: 0.1000A Power: 3.319W

Voltage V: 33.20V PF: 1.000

Optical Parameter (Distance=2.410m) :Equivalent Luminous flux: $\Phi_{\text{eff}} = 373.7\text{lm}$ Efficiency: $\text{Eff} = 112.61\text{lm/W}$

Diffuse angle: @ (25%): 43.2deg @ (50%): 29.1deg @ (75%): 19.8deg @ (50%): 29.1deg

Diffuse angle: @ (25%): 43.2deg @ (50%): 29.1deg @ (75%): 19.8deg @ (50%): 29.1deg

Imax=1177cd (C=0.0deg, G=0.0deg)

C0-180Plane Imax= 1177cd (G=0.0deg)

C0-180Plane I0= 1177cd

		Standar d size	Upper Size limit	Lower size limit	Test result1	Test result2	Test result3	Test result4	Test result5	Test result6	Test result7	Test result8	Jud gme nt	Remarks	
1.Size	diamet er	35			35.02	35	35	35.01	35.02	35.03	35.02	35.01		Test environment: In 20 ℃ -25 ℃ environment to achieve thermal equilibrium after the test.	
	height1	16.5			16.52	16.5	16.5	16.51	16.53	16.49	16.52	16.5			
	height2	2			2.13	2.11	2.14	2.08	2.13	2.12	2.16	2.17			
	Gate shear can not affect the appearance of the lamp														
	See attachment "Appearance Inspection Standards"														
2.Appearance e Quality	See attachment "Appearanc e Inspection Standards"	E	No burr		No burr		No burr		No burr		No burr		OK		
			No stains		No stains		No stains		No stains						
3.Material		PMMA					Color		Transparent				OK		
4.Optical index	Testing LED		CREE 1304(Black bracket bowl)												
	The size and rated power of the light-emitting surface (LES) of the COB recommended by this lens should conform to the parameters in the product basic information table. if it is required to be out of range. According to the heat dissipation capability of the lamp and the actual conditions of the use environment, the lens should be fully tested and tested to prevent the lens life.														
	FWHM		See light distribution curve												
	angle				15.9	15.6	16	16	16	15.5	16.8	15.9			
	-value (CD/L				9.83	#####	9.97	9.96	9.64	9.93	9.68	9.70			
	Efficiency				62.1%	60.7%	62.1%	61.2%	62.9%	62.6%	62.6%	62.6%			
Facula		See the signature sample													
Comprehensive judgment		Qualified													

<div>Remarks:</div> <div>1、Tool Number: V- Vernier Caliper 2D- Quadratic H-Height Gauge M-Tool Microscope P-Needle T-Thick Gauge R- Radius Gauge E- Visual.</div> <div>2、Ambient temperature on the size of the product refer to the table on the right</div>	<div>PMMA product size changes with temperature table</div> <div><div><div>Length changes (mm)</div><div><div><div><div>0.8</div><div>0.7</div><div>0.6</div><div>0.5</div><div>0.4</div><div>0.3</div><div>0.2</div><div>0.1</div><div>0</div></div><div><div>0</div><div>10</div><div>20</div><div>30</div><div>40</div></div></div><div><div><div>Size: 50mm</div><div>Size: 100mm</div><div>Size: 150mm</div><div>Size: 200mm</div><div>Size: 250mm</div><div>Size: 300mm</div></div><div><div>0</div><div>0.1</div><div>0.2</div><div>0.3</div><div>0.4</div><div>0.5</div><div>0.6</div><div>0.7</div><div>0.8</div></div></div><div><div>0</div><div>10</div><div>20</div><div>30</div><div>40</div></div><div>(°C)</div></div></div></div>
<div>Precautions:</div> <div>1. Please wear clean gloves during the lens assembly process to prevent the lens surface from being contaminated.</div> <div>2. Try to avoid touching the total reflection surface when taking the lens.</div> <div>3. The lens surface is contaminated. Only use a soft cotton cloth dipped in analytically pure neutral solvent to wipe gently. Do not wipe with industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA Body, etc.).</div> <div>4. The working temperature of the lens should be within the temperature resistance limit of the lens material. Exceeding the temperature resistance limit will cause the lens to crack or melt and affect the service life of the lens. It is recommended that the upper surface temperature of the LED colloid should be less than 120 degrees.</div>	

1.Size		Standar d size	Upper Size limit	Lower size limit	Test result1	Test result2	Test result3	Test result4	Test result5	Test result6	Test result7	Test result8	Jud gme nt	Remarks
	diamet er	35			35.09	35.08	35.07	35.09	35.12	35.1	35.08	35.08		Test environment: In 20℃ -25℃ environment to achieve thermal equilibrium after the test.
	height1	17			17	17.03	16.99	17.01	17.03	17.04	17.02	17.02		
	height2	2			2.09	2.12	2.1	2.05	2.12	2.1	2.11	2.12		
	Gate shear can not affect the appearance of the lamp													
	See attachment "Appearance Inspection Standards"													
2.Appearance e Quality		See attachment "Appearanc e Inspection Standards"	E	No burr		No burr		No burr		No burr		OK		
				No stains		No stains		No stains		No stains				
3.Material		PMMA					Color		Transparent				OK	
4.Optical index	Testing LED		CREE 1304(Black bracket bowl)											
	The size and rated power of the light-emitting surface (LES) of the COB recommended by this lens should conform to the parameters in the product basic information table. if it is required to be out of range. According to the heat dissipation capability of the lamp and the actual conditions of the use environment, the lens should be fully tested and tested to prevent the lens life.													
	FWHM		See light distribution curve											
	angle				21.2	21.3	21.4	21.5	21.3	21	21.2	21.1		
	-value (CD/L				5.35	5.00	5.00	5.20	5.14	5.14	5.26	5.30		
	Efficiency				84.0%	84.0%	84.6%	84.1%	85.4%	85.7%	85.8%	85.9%		
Facula		See the signature sample												
Comprehensive judgment		Qualified												

<div>Remarks:</div> <div>1、Tool Number: V-Vernier Caliper 2D-Quadratic H-Height Gauge M-Tool Microscope P-Needle T-Thick Gauge R-Radius Gauge E-Visual.</div> <div>2、Ambient temperature on the size of the product refer to the table on the right</div>	<div>PMMA product size changes with temperature table</div> <div><div><div>Length changes (mm)</div><div><div><div><div>0.8</div><div>0.7</div><div>0.6</div><div>0.5</div><div>0.4</div><div>0.3</div><div>0.2</div><div>0.1</div><div>0</div></div><div><div>0</div><div>10</div><div>20</div><div>30</div><div>40</div></div></div><div><div><div>Size: 50mm</div><div>Size: 100mm</div><div>Size: 150mm</div><div>Size: 200mm</div><div>Size: 250mm</div><div>Size: 300mm</div></div><div><div><div>0</div><div>0.1</div><div>0.2</div><div>0.3</div><div>0.4</div><div>0.5</div><div>0.6</div><div>0.7</div><div>0.8</div></div><div><div>0</div><div>10</div><div>20</div><div>30</div><div>40</div></div></div><div><div>0</div><div>10</div><div>20</div><div>30</div><div>40</div></div><div><div>(°C)</div></div></div></div><table><thead><tr><th>Temperature (°C)</th><th>Size: 50mm</th><th>Size: 100mm</th><th>Size: 150mm</th><th>Size: 200mm</th><th>Size: 250mm</th><th>Size: 300mm</th></tr></thead><tbody><tr><td>0</td><td>0.00</td><td>0.00</td><td>0.00</td><td>0.00</td><td>0.00</td><td>0.00</td></tr><tr><td>10</td><td>0.02</td><td>0.04</td><td>0.06</td><td>0.08</td><td>0.10</td><td>0.12</td></tr><tr><td>20</td><td>0.04</td><td>0.08</td><td>0.12</td><td>0.16</td><td>0.20</td><td>0.24</td></tr><tr><td>30</td><td>0.06</td><td>0.12</td><td>0.18</td><td>0.24</td><td>0.30</td><td>0.36</td></tr><tr><td>40</td><td>0.08</td><td>0.16</td><td>0.24</td><td>0.32</td><td>0.40</td><td>0.48</td></tr></tbody></table></div></div>	Temperature (°C)	Size: 50mm	Size: 100mm	Size: 150mm	Size: 200mm	Size: 250mm	Size: 300mm	0	0.00	0.00	0.00	0.00	0.00	0.00	10	0.02	0.04	0.06	0.08	0.10	0.12	20	0.04	0.08	0.12	0.16	0.20	0.24	30	0.06	0.12	0.18	0.24	0.30	0.36	40	0.08	0.16	0.24	0.32	0.40	0.48
Temperature (°C)	Size: 50mm	Size: 100mm	Size: 150mm	Size: 200mm	Size: 250mm	Size: 300mm																																					
0	0.00	0.00	0.00	0.00	0.00	0.00																																					
10	0.02	0.04	0.06	0.08	0.10	0.12																																					
20	0.04	0.08	0.12	0.16	0.20	0.24																																					
30	0.06	0.12	0.18	0.24	0.30	0.36																																					
40	0.08	0.16	0.24	0.32	0.40	0.48																																					
<div>Precautions:</div> <div>1. Please wear clean gloves during the lens assembly process to prevent the lens surface from being contaminated.</div> <div>2. Try to avoid touching the total reflection surface when taking the lens.</div> <div>3. The lens surface is contaminated. Only use a soft cotton cloth dipped in analytically pure neutral solvent to wipe gently. Do not wipe with industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA Body, etc.).</div> <div>4. The working temperature of the lens should be within the temperature resistance limit of the lens material. Exceeding the temperature resistance limit will cause the lens to crack or melt and affect the service life of the lens. It is recommended that the upper surface temperature of the LED colloid should be less than 120 degrees.</div>																																											

		Standard size	Upper Size limit	Lower size limit	Test result1	Test result2	Test result3	Test result4	Test result5	Test result6	Test result7	Test result8	Judgment	Remarks
1.Size	diameter	35			35.06	35.04	35.08	35.07	35.06	35.07	35.08	35.07		Test environment: In 20℃ -25℃ environment to achieve thermal equilibrium after the test.
	height1	16.3			16.34	16.33	16.36	16.36	16.38	16.38	16.36	16.32		
	height2	2			2.09	2.08	2.11	2.1	2.1	2.13	2.08	2.1		
	Gate shear can not affect the appearance of the lamp													
	See attachment "Appearance Inspection Standards"													
2.Appearance Quality		See attachment "Appearance Inspection Standards"	E	No burr		No burr		No burr		No burr		OK		
				No stains		No stains		No stains		No stains				
3.Material		PMMA					Color		Transparent				OK	
4.Optical index	Testing LED		CREE 1304(Black bracket bowl)											
	The size and rated power of the light-emitting surface (LES) of the COB recommended by this lens should conform to the parameters in the product basic information table. if it is required to be out of range. According to the heat dissipation capability of the lamp and the actual conditions of the use environment, the lens should be fully tested and tested to prevent the lens life.													
	FWHM		See light distribution curve											
	angle				29.7	29.6	29.3	29.9	29.1	29.9	29.7	28.5		
	-value (CD/L				3.03	3.38	3.09	3.02	3.16	3.03	3.09	3.24		
	Efficiency				78.4%	77.4%	78.6%	79.3%	79.3%	79.5%	76.7%	75.7%		
	Facula		See the signature sample											
Comprehensive judgment		Qualified												





<div>Remarks:</div> <div>1、Tool Number: V- Vernier Caliper 2D- Quadratic H-Height Gauge M-Tool Microscope P-Needle T-Thick Gauge R- Radius Gauge E- Visual.</div> <div>2、Ambient temperature on the size of the product refer to the table on the right</div>	<div>PMMA product size changes with temperature table</div> <div><div><div>Length changes (mm)</div><div><div><div><div><div>0.8</div><div>0.7</div><div>0.6</div><div>0.5</div><div>0.4</div><div>0.3</div><div>0.2</div><div>0.1</div><div>0</div></div><div><div>0</div><div>10</div><div>20</div><div>30</div><div>40</div></div></div><div><div>Size: 50mm</div><div>Size: 100mm</div><div>Size: 150mm</div><div>Size: 200mm</div><div>Size: 250mm</div><div>Size: 300mm</div></div></div><div><div><div><div><div>0</div><div>10</div><div>20</div><div>30</div><div>40</div></div><div><div>(°C)</div></div></div><table><thead><tr><th>Temperature (°C)</th><th>Size: 50mm</th><th>Size: 100mm</th><th>Size: 150mm</th><th>Size: 200mm</th><th>Size: 250mm</th><th>Size: 300mm</th></tr></thead><tbody><tr><td>0</td><td>0.00</td><td>0.00</td><td>0.00</td><td>0.00</td><td>0.00</td><td>0.00</td></tr><tr><td>10</td><td>0.02</td><td>0.04</td><td>0.06</td><td>0.08</td><td>0.10</td><td>0.18</td></tr><tr><td>20</td><td>0.04</td><td>0.08</td><td>0.12</td><td>0.16</td><td>0.22</td><td>0.35</td></tr><tr><td>30</td><td>0.06</td><td>0.12</td><td>0.18</td><td>0.24</td><td>0.32</td><td>0.52</td></tr><tr><td>40</td><td>0.08</td><td>0.16</td><td>0.24</td><td>0.32</td><td>0.42</td><td>0.72</td></tr></tbody></table></div></div></div></div></div>	Temperature (°C)	Size: 50mm	Size: 100mm	Size: 150mm	Size: 200mm	Size: 250mm	Size: 300mm	0	0.00	0.00	0.00	0.00	0.00	0.00	10	0.02	0.04	0.06	0.08	0.10	0.18	20	0.04	0.08	0.12	0.16	0.22	0.35	30	0.06	0.12	0.18	0.24	0.32	0.52	40	0.08	0.16	0.24	0.32	0.42	0.72
Temperature (°C)	Size: 50mm	Size: 100mm	Size: 150mm	Size: 200mm	Size: 250mm	Size: 300mm																																					
0	0.00	0.00	0.00	0.00	0.00	0.00																																					
10	0.02	0.04	0.06	0.08	0.10	0.18																																					
20	0.04	0.08	0.12	0.16	0.22	0.35																																					
30	0.06	0.12	0.18	0.24	0.32	0.52																																					
40	0.08	0.16	0.24	0.32	0.42	0.72																																					
<div>Precautions:</div> <div>1. Please wear clean gloves during the lens assembly process to prevent the lens surface from being contaminated.</div> <div>2. Try to avoid touching the total reflection surface when taking the lens.</div> <div>3. The lens surface is contaminated. Only use a soft cotton cloth dipped in analytically pure neutral solvent to wipe gently. Do not wipe with industrial solvents (alcohol, isopropanol, acetone, ether, toluene, xylene, carbon tetrachloride, MMA Body, etc.).</div> <div>4. The working temperature of the lens should be within the temperature resistance limit of the lens material. Exceeding the temperature resistance limit will cause the lens to crack or melt and affect the service life of the lens. It is recommended that the upper surface temperature of the LED colloid should be less than 120 degrees.</div>																																											

PN		HK-WY-35@16-15-D6-21-1g-1-V		Product Name	HK Peak 35@16-15 °lens(V)		
Product material		PMMA					
Package diagram		<div><p>Single Vacuum package Box package</p></div>					
Product packing		32	A/ Box	4	pcs/Layer		
		14	Layer/Box	1288	A/ Carton		
Packaging Materials	NO.	Part No	Part name	Size	Dosage	Unit	Remarks
	1	2.07.0075	Blister box	23cm*21cm	56	BAG	
	2	2.08.0001	PE film	30cm*30cm	56	PCS	
	3	2.06.0005	Reel label paper	6.2cm*8cm	56	PCS	
	4	2.06.0005	Box label paper	6.2cm*9.2cm	1	PCS	
	5	2.06.0003	big plate	46.8cm*42.8cm	15	PCS	
	6	2.06.0015	big flat carton	48cm*44cm*19cm	1	PCS	
Remarks	The loose packing is not subject to this specification. Customer's requirements shall prevail						

Special notice

When glue pass through holes, columns and other structures, or part of the thin structure, will form a weld line. The product which uses multi-point injection welding line will appear because of the combination of sol, as shown below:

Synthesis



Please note :

The appearance of lines in the structure of the product as well as at the screw hole is a normal phenomenon, will not affect the actual use of the product, and can not be avoided at this stage.

Appearance inspection standards

1 Operating procedures

1.1.1 Sampling standards, sampling plan and AQL

Test level: GB/T2828.1-2012 The first part is according to the acceptance quality limit (AQL) retrieval batch inspection sampling plan, general inspection level II level, CR class defect coefficient 0, MA defect rejection level AQL = 0.65, MI class defect rejection level AQL = 1.0; defect level please see 5.4.

2 Code table

Code	Code description	Unit	Code		Code description	Unit
N	Amount/pcs	pcs	D		Diameter	mm
L	Length	mm	H		Depth	mm
W	Width	mm	DS		Distance	mm
S	Proportion	mm ²	SS		Offset	mm

3 Test conditions

3.1 Sight distance and working hours: Sight distance should be 30-35cm, each side of the inspection time does not exceed 12s, the visual angle of 45-135 degrees;

3.2 Light: 2x40w cool white fluorescent lamp, the light source is 500-550mm away from the lens surface; in order to make the appearance defect can be correctly recognized, the illumination should be 500-1000Lux, and the observation time is 10 seconds.

3.3 Visual inspection staff should be 1.0 (including corrected visual acuity) above, no color blindness, color weakness.

4 Appearance inspection standards

Test items	Judging standard	Inspection equipment	Defect level		
		Testing method	MI	MA	CR
Check the sample	When start the machine and process, all products have to check the appearance of the sample, the appearance of the sample is divided into qualified samples and limited samples.	Sample comparison , visual			√
	1: Qualified sample refers to the appearance and structure standard of the product which recognized by the client, the sample size should be confirmed before mass production;				

	2: The limited sample refers to the limit of a particular exceptionally developed sample. Limit the sample only for its specific point of exception to confirm; The priority is higher than the other criteria in this table. When there is a limited sample, the limit sample shall prevail.				
Raw edge	Not allowed to affect the size and assembly	Visual, point card		√	
Scratch	1: Non-optical surface and non-exposed surface scratches should be visually insignificant and the length is less than 1/10 of the maximum surface size.	Visual, point card, calipers		√	
Fingerprint	Fingerprints are not allowed on all products	Visual		√	
Foreign objects, black spots, white spots	The product may not be attached to foreign objects, including oil, fiber, dregs of water gap and so on				√
Deformation	Insufficient filling shall not affect the appearance of the assembly and the exposed surfaces.	Visual, feeler			√
Poor ejection	Products may not appear bad ejection, including no convex top, thimble printed on the assembly surface shall not be higher than the product surface, non-assembled surface thimble height should not exceed the product size tolerances; thimble printing should be less than the product surface and no more than 0.3; thimble surface treatment should be consistent with the product side.	Visual, point card		√	
	Ejection strain: the optical surface and the appearance of the exposed surface after assembly are not allowed to have a strain, and the structural surface does not allow visual obvious strain.				
Insufficient filling	Insufficient filling shall not affect the appearance of the assembly and the exposed surfaces, The signature sample shall prevail.	Visual, point card		√	
Shrink	When the entire surface of the product shrinks, the optical properties and dimensions must meet the requirements, and the visual will not significantly affect the appearance. Part shrink reference point defects	Visual, point card		√	
Flow marks、Welding line	1: Product does not allow the presence of flow marks and welding lines unless the structure can not be avoided;	Visual		√	
	2: The remaining flow marks shall not appear in the optical surface, a single $L \leq 10\text{mm}$, no more than two				

Bubble	No bubbles are allowed	Visual		√	
Foreign objects, black spots, white spots	Not obvious or $D \leq 0.3\text{mm}$ black spots and foreign bodies in the area of 100x100mm not more than 1; Exceeded foreign matter black spots is judged bad.	Visual, point card	√		
Damaged	No damage is allowed	Visual			√
Cold glue	Optical surface may not have cold glue, non-optical surface cold glue should meet the visual is not obvious.	Visual	√		
Bad incision	1: Do not affect the product size, shall not penetrate the optical surface, the cut should be smooth;	Visual			√
	2: Laser cutting products, the optical surface burns shall not occur after the processing is completed. Beading must not affect product installation				
	3: Three molds and hot runner gate shall not appear residue.				
Scrub	Scrub surface should be uniform, off the scrub phenomenon should not be obvious , A single off scrub imprint requires $D \leq 1\text{ mm}$ and no more than 1 area within a 50x50 mm area	Visual		√	